

Specification Sheet

Part Number: 156-01807



Delivers high extraction force for reliable performance, yet it's easy to install.
Reusable fastener can be removed from threaded or nonthreaded holes using a 5/16" hex driver.
Heat stabilized material provides excellent resistance to high temperatures.

Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 6", 50lb, PA66HS, Black, 500/bag

Article Number	156-01807
Type	T50SOSBHMB
Color	Black (BK)
Quantity Per	bag
Product Description	HellermannTyton Blind Hole Mount Cable Ties for threaded and nonthreaded holes offer an easy-to-use method for bundling and affixing cables. The 2-piece design includes a heat stabilized cable tie and formula-matched, 1/4" mount that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or nonthreaded blind holes. Mount can slide along cable tie to adjust orientation if needed. Fastener can be removed from hole using a hex driver. This ensures fastener can be reused.

Short Description	Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 6", 50lb, PA66HS, Black, 500/bag
Global Part Name	T50SOSBHMB-PA66HS-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	6.0
Length L (Metric)	150.0
Identification Plate Position	none
Width W (Imperial)	0.31
Width W (Metric)	7.8
Bundle Diameter Min (Imperial)	0.10
Bundle Diameter Min (Metric)	2.5
Bundle Diameter Max (Imperial)	1.40
Bundle Diameter Max (Metric)	35.0
Height H (Imperial)	0.736
Height H (Metric)	18.7

Diameter D (Imperial)	0.25
Diameter D (Metric)	6.35
Mounting Hole Diameter D (Imperial)	0.25
Mounting Hole Diameter D (Metric)	6.35 mm
Mounting Hole Diameter D Min (Imperial)	0.246
Mounting Hole Diameter D Max (Imperial)	0.254
Mounting Hole Diameter D Max (Metric)	6.45

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Material Cable Tie Polyamide 6.6 heat stabilized (PA66HS)

Flammability UL 94 V-2

UV Resistant (Yes/No) No

Operating Temperature -40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988