

Specification Sheet

Part Number: 156-02884



MOC stud mount secures bundles above a bolt or stud. Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Independent rotation allows for adjustable routing orientation.

High-performance stud mount design allows for easy installation and delivers outstanding stud retention to keep bundles secure.

Stud Mount to MOC Clip, 22mm Clip Above Mount, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 2000/ctn

| | |
|---------------------|--|
| Article Number | 156-02884 |
| Type | SMFMOC22M |
| Color | Black (BK) |
| Quantity Per | bag |
| Product Description | The MOC with stud mount features HellermannTyton's unique retention clip with a best-in-class stud mount to secure to a 5mm or 6mm stud or bolt. The mount delivers a low insertion force while exhibiting high extraction resistance for a secure mounting point. |
| Short Description | Stud Mount to MOC Clip, 22mm Clip Above Mount, 5mm/6mm Stud Mount, PA66HIRHSUV, Black, 2000/ctn |

Global Part Name SMFMOC22M-PA66HIRHSUV-BK

Length L (Imperial) 1.44

Length L (Metric) 36.5

Fixation Method Stud Mount

Bundle Diameter Min (Imperial) 0.79

Bundle Diameter Min (Metric) 20.0

Bundle Diameter Max (Imperial) 0.98

Bundle Diameter Max (Metric) 25.0

Height H (Imperial) 2.03

Height H (Metric) 51.6

Depth D (Imperial) 0.59

Depth D (Metric) 15.0

Nominal Diameter (Metric) 22.0

Stud Diameter (Metric) 5.0 mm 6.0 mm

Stud Diameter (Imperial) 0.20 ";0.24

| | |
|------------------------------|--|
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | No |
| Package Quantity (Imperial) | 2000 |
| Package Quantity (Metric) | 2000 |
| Customs Number | 3926909988 |