

Specification Sheet

Part Number: 156-04192



One-piece ratchet clamp can be pre installed, conveniently adding wires at installation or a later time.

A quick, toolless, one-handed installation. Releasable function to allow for adjusting or adding wire.

Clamp saddle provides additional routing option using a cable tie, eliminating the need to drill or add complex routing parts.

Impact modified, heat and UV stabilized PA66 provides long-term durability in hazardous solar conditions.

Nextracker-specific stainless steel mounting hanger designed for severe conditions of single axis tracker movement.

NexTracker Inline Ratchet Clamp Torque Tube Hanger, 0.50 - 0.77" Bundle Dia, PA66HIRHSUV/SS, Black, 200/ctn

Article Number	156-04192
Type	IRCBNEXTT
Color	Black (BK)
Quantity Per	box

Product Description	The Nextacker Inline Ratchet Clamp Torque Tube Solar Hanger offers one-handed, toolless simplicity and size versatility for managing wires and cables on solar modules. The robust design and solar-optimized materials make it ideal for heavy duty, outdoor applications. The one-piece adjustable clamp can be closed by hand to the desired diameter, replacing multiple sizes for fixed diameter fasteners. The integrated release feature enables easy and nondestructive removal of cables by inserting a flat-head screwdriver. This allows the clamp to be reused without removing it.
Short Description	NexTracker Inline Ratchet Clamp Torque Tube Hanger, 0.50 - 0.77" Bundle Dia, PA66HIRHSUV/SS, Black, 200/ctn
Global Part Name	IRCBNEXTT-PA66HIRHSUV/SS304-BK
Minimum Tensile Strength (Imperial)	25.0
Minimum Tensile Strength (Metric)	110.0
Length L (Imperial)	3.15
Length L (Metric)	79.9
Fixation Method	Mounting Hanger
Releasable Closure	Yes
Width W (Imperial)	1.37
Width W (Metric)	34.8
Bundle Diameter Min (Imperial)	0.50
Bundle Diameter Min (Metric)	12.7

Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.6
Height H (Imperial)	2.19
Height H (Metric)	55.5
Cable Tie Width Max (Imperial)	0.52
Material	Stainless Steel (SS304) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	SS304 PA66HIRHSUV
Flammability	UL 94 HB
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	200
Package Quantity (Metric)	200

Customs Number

3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)