


Specification Sheet

Part Number: 157-00293



Covers top of stud for protection from stud end.
Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.
PA46 material option allows use in high-heat applications.

M8 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA46, Brown, 1500/pkg

Article Number	157-00293
Type	T80ROSSB8U
Color	Brown (BN)
Quantity Per	carton
Product Description	Stud Mount Ties offer outstanding stud retention. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.
Short Description	M8 Stud Mount Tie, 7.5" Tie, 80lb Tensile Strength, PA46, Brown, 1500/pkg

Global Part Name	T80ROSSB8U-PA46-BN
------------------	--------------------

Minimum Tensile Strength (Imperial)	80.0
-------------------------------------	------

Minimum Tensile Strength (Metric)	355
-----------------------------------	-----

Length L (Imperial)	8.3
---------------------	-----

Length L (Metric)	212.0
-------------------	-------

Fixation Method	Stud Mount
-----------------	------------

Identification Plate Position	none
-------------------------------	------

Releasable Closure	No
--------------------	----

Tie Closure	plastic pawl
-------------	--------------

Width W (Imperial)	0.70
--------------------	------

Width W (Metric)	17.75
------------------	-------

Bundle Diameter Min (Imperial)	0.14
--------------------------------	------

Bundle Diameter Min (Metric)	3.5
------------------------------	-----

Bundle Diameter Max (Imperial)	1.97
--------------------------------	------

Bundle Diameter Max (Metric)	50.0
------------------------------	------

Cable Ties	157-00293
------------	-----------

Height H (Imperial)	0.59
Height H (Metric)	15.0
Mounting Hole Diameter D (Imperial)	0.31" x 0.05
Mounting Hole Diameter D (Metric)	M8 x 1.25
Stud Diameter (Metric)	8.0 mm
Stud Diameter (Imperial)	0.31
Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +266°F (-40°C to +130°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1500
Package Quantity (Metric)	1500

Customs Number

3926909988