

Specification Sheet

Part Number: 157-00419



Low-profile head allows mounts to stack, providing more mounting versatility from a single stud
Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure

Low Profile M10 Stud Mount Tie, 7.5" L, 80lb Tensile, PA66HIRHSUV, Black, 100/pkg

Article Number	157-00419
Type	T80ROSLPSB10U
Color	Black (BK)
Quantity Per	bag
Product Description	One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.
Short Description	Low Profile M10 Stud Mount Tie, 7.5" L, 80lb Tensile, PA66HIRHSUV, Black, 100/pkg

Global Part Name	T80ROSLPSB10U-PA66HIRHSUV-BK
------------------	------------------------------

Minimum Tensile Strength (Imperial)	80.0
-------------------------------------	------

Minimum Tensile Strength (Metric)	335.0
-----------------------------------	-------

Length L (Imperial)	8.5
---------------------	-----

Length L (Metric)	215.0
-------------------	-------

Fixation Method	Weld Stud Fixing
-----------------	------------------

Identification Plate Position	none
-------------------------------	------

Releasable Closure	No
--------------------	----

Tie Closure	plastic pawl
-------------	--------------

Width W (Imperial)	0.23
--------------------	------

Width W (Metric)	5.52
------------------	------

Bundle Diameter Min (Imperial)	0.14
--------------------------------	------

Bundle Diameter Min (Metric)	3.5
------------------------------	-----

Bundle Diameter Max (Imperial)	1.97
--------------------------------	------

Bundle Diameter Max (Metric)	50.0
------------------------------	------

Height H (Imperial)	0.05
---------------------	------

Height H (Metric)	1.35
Stud Diameter (Metric)	M10
Stud Diameter (Imperial)	M10
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)