

Specification Sheet

Part Number: 166-90098

External NPT thread provides a secure connection.

Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.

Elbow features a smooth, swept bore to ease cable installation.

All-around "teeth" attach firmly to conduit and deliver a high extraction force.



Durable nylon material has high resistance to salts, oils, weak acids and solvents.

IP66 fitting has one-piece construction.

HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, NPT Thread, 0.50" Dia, PA66, Black, 10/pkg

Article Number 166-90098

Type HG050-90-0500

Color Black (BK)

Quantity Per bag

Product Description HelaGuard Non-Metallic 90-Degree Elbow fitting features a snap-on

design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak

acids and solvents. Designed for easy removal with a small

screwdriver. IP66 ingress protection rated fittings.

Short Description	HelaGuard Non-Metallic IP66 Fitting, 90-Elbow, NPT Thread, 0.50" Dia, PA66, Black, 10/pkg
Global Part Name	HG050-90-0500-PA66-BK
Length L (Imperial)	2.09
Length L (Metric)	53
Variant	90° Elbow
Outside Diameter OD (Imperial)	1.26
Outside Diameter OD (Metric)	32
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	21
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes

No

UV Resistant (Yes/No)

Operating Temperature

-58°F to +275°F (-50°C to +135°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity (Imperial)

10

Package Quantity (Metric)

10

3926909988

© 2023 HellermannTyton. All Rights Reserved.

Customs Number

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions