

Specification Sheet

Part Number: 166-90108



External NPT thread provides a secure connection.
Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.
All-around "teeth" attach firmly to conduit and deliver a high extraction force.
Durable nylon material has high resistance to salts, oils, weak acids and solvents.
IP66 fitting has one-piece construction.

HelaGuard Non-Metallic IP66 Fitting, Straight, NPT Thread, 1.50" Dia, PA66, Black, 2/pkg

Article Number	166-90108
Type	HG150-S-1500
Color	Black (BK)
Quantity Per	bag
Product Description	HelaGuard Non-Metallic Straight fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP66 ingress protection rated fittings.

Short Description	HelaGuard Non-Metallic IP66 Fitting, Straight, NPT Thread, 1.50" Dia, PA66, Black, 2/pkg
Global Part Name	HG150-S-1500-PA66-BK
Length L (Imperial)	2.64
Length L (Metric)	67
Variant	Straight
Outside Diameter OD (Imperial)	2.99
Outside Diameter OD (Metric)	76
Nominal Diameter (Imperial)	2.13
Nominal Diameter (Metric)	54
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
UV Resistant (Yes/No)	No

Operating Temperature	-58°F to +275°F (-50°C to +135°C)
-----------------------	-----------------------------------

Reach Compliant (Article 33)	Yes
------------------------------	-----

ROHS Compliant	Yes
----------------	-----

UL Recognized (US)	Yes
--------------------	-----

UL Recognized (US and Canada)	Yes
-------------------------------	-----

Package Quantity (Imperial)	2
-----------------------------	---

Package Quantity (Metric)	2
---------------------------	---

Customs Number	3926909988
----------------	------------