

Specification Sheet

Part Number: 166-90210

Very high impact strength; recovers completely if crushed and provides excellent fatigue life.

Highly UV resistant; suitable for use in outdoor applications.

Offered in fine or course corrugated pitch.

Offered with or without slit; slit options offer easy access during installation and maintenance.



HelaGuard Non-Metallic Conduit, Std. Weight, 0.75" Dia, Nylon PA12, Black, 100 ft/Std. Reel

Article Number 166-90210

Type HG-HI0750

Color Black (BK)

Quantity Per reel

Product Description
A standard weight corrugated conduit made of PA12 nylon that offers superior impact resistance, making it ideal for protecting wire and cable bundles in conditions with continual movement or bending. This material is highly resistant to UV light, solvents and oils. Combine with HelaGuard Non-Metallic Fittings to achieve IP66 or greater protection against water, wind and dirt.

Short Description
HelaGuard Non-Metallic Conduit, Std. Weight, 0.75" Dia, Nylon PA12, Black, 100 ft/Std. Reel

| | |
|--------------------------------|--|
| Global Part Name | HG-HI0750-PA12-BK |
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.5 |
| Inner Diameter D (Imperial) | 0.86 |
| Inner Diameter D (Metric) | 21.7 |
| Outside Diameter OD (Imperial) | 1.13 |
| Outside Diameter OD (Metric) | 28.5 |
| Nominal Diameter (Imperial) | 0.75 |
| Nominal Diameter (Metric) | 28 |
| Material | Polyamide 12 (PA12) |
| Material Shortcut | PA12 |
| Flammability | Self-extinguishing according to EN IEC 61386 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |

Operating Temperature -58°F to +230°F (-50°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 100

Package Quantity (Metric) 30.48

Customs Number 3926909988

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)