

Specification Sheet

Part Number: 166-90828



Integrated Sealing Technology creates a true, one-piece component that reduces installation time and provides error free installation.

Nickel plated brass metric thread provides a secure connection even under dynamic conditions.

Swivel thread feature minimizes cable twisting and provides strain relief.

All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force.

Fittings deliver IP68 ingress protection against moisture and dirt.

HelaGuard NM 28mm IP68 Ultra Fitting, 90-Elbow Brass Swivel, Ext M32 Thread, NPB, PA66, Black, 10/pkg

Article Number 166-90828

Type HGU34-90M-M32B

Color Black (BK)

Quantity Per pack

Product Description Straight snap-on style fittings with nickel plated brass metric threaded fitting provides a true, one-piece component solution; seals are integrated into the fitting body. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids and solvents. Designed for fast assembly and easy removal using a small screwdriver.

| | |
|------------------------------|---|
| Short Description | HelaGuard NM 28mm IP68 Ultra Fitting, 90-Elbow Brass Swivel, Ext M32 Thread, NPB, PA66, Black, 10/pkg |
| Global Part Name | HGU34-90M-M32B-NPB/PA66-BK |
| Length L (Imperial) | 3.11 |
| Length L (Metric) | 79 |
| Variant | 90° Elbow |
| Nominal Diameter (Imperial) | 1 |
| Nominal Diameter (Metric) | 34 |
| Material | Nickel Plated Brass (NPB) Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 NPB |
| Flammability | Self-extinguishing |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -58°F to +275°F (-50°C to +135°C) |
| Reach Compliant (Article 33) | No |

| | |
|-----------------------------|------------|
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 10 |
| Package Quantity (Metric) | 10 |
| Customs Number | 7412200000 |