## **HellermannTyton**

## **Specification Sheet**

Part Number: 166-90874

Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability. True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits.

All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force.



PA66 nylon material has high resistance to salts, oils, weak acids, and solvents.

Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.

HelaGuard Non-Metallic Ultra IP68 Fitting, Straight, 0.75" NPT Thread, 0.75" Dia, PA66, Black, 50/box

Article Number 166-90874

Type HGU075-S-0750

Color Black (BK)

Quantity Per EA

| Product Description  Straight Snap-On style Metric or NPT threaded nylon fitting a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical rest against salts, oils, weak acids, and solvents. Designed for exemoval with a small screwdriver. UL-Listed fittings deliver IP67 + IP68 + IP69 ingress protection. | re<br>istance<br>easy |
|--|-----------------------|
| Short Description HelaGuard Non-Metallic Ultra IP68 Fitting, Straight, 0.75" N<br>Thread, 0.75" Dia, PA66, Black, 50/box   | IPT                   |
| Global Part Name HGU075-S-0750-PA66-BK   |                       |
| Length L (Imperial) 1.93   |                       |
| Length L (Metric) 49   |                       |
| Variant Straight   |                       |
| Outside Diameter OD (Imperial) 1.73  |                       |
| Outside Diameter OD (Metric) 44.0  |                       |
| Nominal Diameter (Imperial) 0.75   |                       |
| Nominal Diameter (Metric) 28   |                       |
|  |                       |
| Material Polyamide 6.6 (PA66)  |                       |

Material Shortcut PA66

Flammability Self-extinguishing

Halogen Free Yes

UV Resistant (Yes/No) No

Operating Temperature -58°F to +275°F (-50°C to +135°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3926909988

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions