HellermannTyton

Specification Sheet

Part Number: 167-00220

Living hinge allows harness serviceability and reduces assembly time. Internal ribs affix to exterior of tubing which prevents slipping during tension or movement.

Snap-on connection makes installations quick and easy and increases efficiencies in harness assembly.

Junction point outlets offer additional areas to branch off wires and prevents wires from sliding or accidental removal from tubing.

Improves aesthics of assembled wire harness.

No tools required to disassemble.



Hinged Convoluted Tubing T-Fitting, L- 0.75" x C- 0.75" x R- 0.75", PP, Black, 200/pkg

Article Number 167-00220

Type CTHC-T777

Color Black (BK)

Quantity Per carton

Product Description	Convoluted Loom fittings are single piece hinged connectors that simply snap-on over slit and unslit loom tubing to secure wire branchouts or, connect different tubing diameters. The unique wrap around design makes installation easier and more efficient, while the unique junction points make easy branchouts that keep wires from sliding out of the tubing and eliminates need for secondary taping operation. The polypropylene material creates a sleek assembly and improves the appearance of the entire wiring assembly.
Short Description	Hinged Convoluted Tubing T-Fitting, L- 0.75" x C- 0.75" x R- 0.75", PP, Black, 200/pkg
Global Part Name	CTHC-T777-PP-BK
Variant	Fittings
Inner Diameter D (Imperial)	0.75
Inner Diameter D (Metric)	19.1
Diameter D (Imperial)	0.75
Diameter D (Metric)	19.1
Material	Polypropylene (PP)

Flammability UL 94 HB

PP

Halogen Free Yes

Material Shortcut

UV Resistant (Yes/No) No

Operating Temperature -4°F to +194°F (-20°C to +90°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 200

Package Quantity (Metric) 200

Customs Number 3926909988

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions