

Specification Sheet


Part Number: 169-60122

Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.

Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Excellent flame resistant properties with higher operating temperature range than PE tubings.



Convoluted Tubing, Split, 0.43" Dia, PP-FR, Orange, 1400 ft/carton

Article Number	169-60122
Type	CTPPFR716
Color	Orange (OG), High Voltage (HV)
Quantity Per	carton

Product Description	<p>HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires. Available in a variety of materials providing a range of flame resistance and operating temperatures.</p>
Short Description	Convoluted Tubing, Split, 0.43" Dia, PP-FR, Orange, 1400 ft/carton
Global Part Name	CTPPFR716-PPFR-OG
Length L (Imperial)	1400.0
Length L (Metric)	426.7
Variant	Slit
Inner Diameter D (Imperial)	0.437
Inner Diameter D (Metric)	11.10
Diameter D (Imperial)	0.597
Diameter D (Metric)	15.16
Outside Diameter OD (Imperial)	0.597
Outside Diameter OD (Metric)	15.16
Nominal Diameter (Imperial)	7/16

Nominal Diameter (Metric)	11.13
Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127
Material	Polypropylene, flame retardant (PPFR)
Material Shortcut	PPFR
Flammability	UL 94 V-2
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1400
Package Quantity (Metric)	426.72
Customs Number	3926909988

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)