


Specification Sheet

Part Number: 170-03090



Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Braided Sleeving, Expandable, Flame Retardant, 0.25" Dia, PET, Black, 1000 ft/bulk reel

Article Number	170-03090
Type	BSPFR140B
Color	Black (BK)
Quantity Per	reel
Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
Short Description	Braided Sleeving, Expandable, Flame Retardant, 0.25" Dia, PET, Black, 1000 ft/bulk reel
Global Part Name	BSPFR140B-PET-BK

Length L (Imperial) 1000.0

Length L (Metric) 304.8

Bundle Diameter Min (Imperial) 0.125

Bundle Diameter Min (Metric) 3.2

Bundle Diameter Max (Imperial) 0.437

Bundle Diameter Max (Metric) 11.1

Diameter D (Imperial) 0.25

Diameter D (Metric) 6.4

Nominal Diameter (Imperial) 0.25

Nominal Diameter (Metric) 6.4

Material Polyester (PET)

Material Shortcut PET

Flammability FMVSS 302 Mil-202 FAR 25 UL VW-1

Halogen Free Yes

UV Resistant (Yes/No)	No
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL 94 VW-1
UL Recognized (US)	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	304.80
Customs Number	5808100000

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)