

Specification Sheet

Part Number: 170-03148

Flexible construction that conforms to irregular shapes and contours. Hook and loop feature wraps over cable bundle allowing future access to cables.

Easy access saves assembly time and allows for easy splicing or insertion of additional wires.

PET yarn construction offers excellent protection against cuts and abrasions.



Braided Sleeving, Hook & Loop, 0.5" Dia, PET, Black, 100 ft/bulk reel

| | |
|---------------------|--|
| Article Number | 170-03148 |
| Type | BSHKLP120B |
| Color | Black (BK) |
| Quantity Per | reel |
| Product Description | Designed for the quick and easy management of wires, this expandable sleeving has an internal hook and loop strap that is able to adhere to its outer PET braid, delivering flexibility that allows it to fit around odd-shaped connectors. Its color-matched hook and loop closure provides for an easy on and off installation, as well as instant and convenient access for harness break-outs and networks. the primary application for this sleeving is the wrapping and bunching of cables in a deployed situation or when frequent access to cables is necessary. |

| | |
|--------------------------------|---|
| Short Description | Braided Sleeving, Hook & Loop, 0.5" Dia, PET, Black, 100 ft/bulk reel |
| Global Part Name | BSHKLP120B-PET-BK |
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.48 |
| Bundle Diameter Min (Imperial) | 0.1 |
| Bundle Diameter Min (Metric) | 2.54 |
| Bundle Diameter Max (Imperial) | 0.5 |
| Bundle Diameter Max (Metric) | 12.7 |
| Diameter D (Imperial) | 0.50 |
| Diameter D (Metric) | 12.7 |
| Nominal Diameter (Imperial) | 0.5 |
| Nominal Diameter (Metric) | 12.7 |
| Wall Thickness WT (Imperial) | 0.025 |
| Wall Thickness WT (Metric) | 0.635 |

| | |
|------------------------------|-----------------------------------|
| Material | Polyester (PET) |
| Material Shortcut | PET |
| Flammability | UL 94 V-0 FAR 25 |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -94°F to +257°F (-70°C to +125°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 30.48 |
| Customs Number | 5808100000 |