

Specification Sheet

Part Number: 170-03215



Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.

Unique construction retains shape and rigidity throughout unrolling.

Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.

Braided Sleeving, Split Wrap, 1" Dia, PET, Black, 10 ft/pkg

Article Number 170-03215

Type BSPSW100

Color Black (BK)

Quantity Per pack

Product Description A lateral split semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.

Short Description Braided Sleeving, Split Wrap, 1" Dia, PET, Black, 10 ft/pkg

Global Part Name BSPSW100-PET-BK

Length L (Imperial)	10.0
Length L (Metric)	3.05
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	1.0
Bundle Diameter Max (Metric)	25.4
Diameter D (Imperial)	1.0
Diameter D (Metric)	25.4
Nominal Diameter (Imperial)	1
Nominal Diameter (Metric)	25.4
Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL 94 V-0
Halogen Free	Yes

UV Resistant (Yes/No)	No
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	10.0
Package Quantity (Metric)	3.05
Customs Number	5808100000

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)