HellermannTyton

Specification Sheet

Part Number: 181-00142

A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.

Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Article Number 181-00142

Type SDA.75X.75

Color White (WH)

Quantity Per carton

Product Description HellermannTyton Solid Wall Wiring Duct efficiently routes and

protects wire. Solid wall wiring duct is designed for straight wire runs

where breakouts are not required. Solid wall wiring duct is

manufactured from high-impact, rigid PVC; comes in standard colors

of white, gray and black; and is available in 6-foot lengths.

Short Description Solid Wall Wiring Duct, 0.75" x .75", Adhesive, PVC, White,

120ft/Carton

Global	Dart	Nama
Cilluai	ган	manne

SDA.75X.75-PVC-WH

Length L (Imperial)	6.0	
Length L (Metric)	1.83	
Fixation Method	Adhesive	
Width W (Imperial)	0.75	
Width W (Metric)	19.1	
Height H (Imperial)	0.8	
Height H (Metric)	20.3	
Mounting Hole Centers (Imperial)	4.0	
Material	Polyvinylchloride (PVC)	
Material Shortcut	DVC	

Material Shortcut PVC

Flammability Self-extinguishing

Halogen Free No

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Certification/Specification EN 50085-1:2005 + A1:2013 UL EN 50085-2-3_1A CSA

UL Recognized (US) Yes

Package Quantity (Imperial) 120.0

Package Quantity (Metric) 36.58

Customs Number 3925900000

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions