

## **Specification Sheet**

Part Number: 181-00615

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC, Black, 120ft/Carton

Article Number 181-00615

Type SLHD3X3

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features

narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and

components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC,

Black, 120ft/Carton

$\sim$ 1 $\sim$ 1	<b>D</b> (	N 1	
Global	Part	Name	į

SLHD3X3-PVC-BK

Length L (Imperial)

6.0

Length L (Metric)

1.83

**Fixation Method** 

Non-Adhesive

Width W (Imperial)

3.0

Width W (Metric)

76.2

Height H (Imperial)

3.07

Height H (Metric)

77.9

Mounting Hole Centers (Imperial)

2.0

Material

Polyvinylchloride (PVC)

**Material Shortcut** 

PVC

Flammability

Self-extinguishing

Halogen Free

No

**Operating Temperature** 

+122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 120.0

Package Quantity (Metric) 36.58

Customs Number 3925900000

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions