

Specification Sheet

Part Number: 181-22013

Solid wall construction provides excellent coverage to keep wires clean. Durable material protects wires from damage, with long-lasting performance.

Available standard colors complement or contrast in light and dark environments.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

Solid Wall Wiring Duct, 2" x 2", Non-Adhesive, PVC, White, 120ft/Carton

Article Number 181-22013

Type SD2X2

Color White (WH)

Quantity Per carton

Product Description HellermannTyton Solid Wall Wiring Duct efficiently routes and

protects wire. Solid wall wiring duct is designed for straight wire runs

where breakouts are not required. Solid wall wiring duct is

manufactured from high-impact, rigid PVC; comes in standard colors

of white, gray and black; and is available in 6-foot lengths.

Short Description Solid Wall Wiring Duct, 2" x 2", Non-Adhesive, PVC, White,

120ft/Carton

Global	Dart	Nama
Cilluai	ган	manne

SD2X2-PVC-WH

Length L (Imperial)

6.0

Length L (Metric)

1.83

Fixation Method

Non-Adhesive

Width W (Imperial)

2.0

Width W (Metric)

50.8

Height H (Imperial)

2.07

Height H (Metric)

52.6

Mounting Hole Centers (Imperial)

4.0

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Flammability

Self-extinguishing

Halogen Free

No

Operating Temperature

+122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Certification/Specification CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL

UL Recognized (US) Yes

Package Quantity (Imperial) 120.0

Package Quantity (Metric) 36.58

Customs Number 3925900000

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions