

Specification Sheet

Part Number: 181-32007



- Strong fingers prevent unwanted breaking.
- Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
- Supplied with mounting holes to streamline installation.
- Optional covers enhance protection and appearance.

Slotted Wall Wiring Duct, 3" x 2", Non-Adhesive, PVC, Gray, 140ft/Carton

Article Number 181-32007

Type SL3X2

Color Gray (GY)

Quantity Per carton

Product Description HellermannTyton Slotted Wall Wiring Duct features break-away fingers that provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and T's.

Short Description Slotted Wall Wiring Duct, 3" x 2", Non-Adhesive, PVC, Gray, 140ft/Carton

Global Part Name	SL3X2-PVC-GY
Length L (Imperial)	7.0
Length L (Metric)	2.13
Width W (Imperial)	3.0
Width W (Metric)	76.2
Height H (Imperial)	2.07
Height H (Metric)	52.6
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-extinguishing
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes

Certification/Specification EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL CSA

UL Recognized (US) Yes

Package Quantity (Imperial) 140

Package Quantity (Metric) 42.7

Customs Number 3925900000

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)