

Specification Sheet

Part Number: 181-33050



- Strong fingers prevent unwanted breaking.
- Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
- Supplied with mounting holes to streamline installation.
- Optional covers enhance protection and appearance.

Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC, Gray, 7FT, 70 ft/carton

Article Number 181-33050

Type SL3X3

Color Gray (GY)

Quantity Per carton

Product Description HellermannTyton Slotted Wall Wiring Duct features break-away fingers that provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and T's.

Short Description Slotted Wall Wiring Duct, 3" x 3", Non-Adhesive, PVC, Gray, 7FT, 70 ft/carton

Global Part Name	SL3X3-PVC-GY
Length L (Imperial)	7
Length L (Metric)	2.13
Fixation Method	Non-Adhesive
Width W (Imperial)	3.00
Width W (Metric)	76.20
Height H (Imperial)	3.07
Height H (Metric)	77.90
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride - rigid extrusion grade (PVC)
Material Shortcut	PVC
Flammability	Self-extinguishing
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No

ROHS Compliant Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 70

Package Quantity (Metric) 21.3

Customs Number 3926909988