

Specification Sheet

Part Number: 181-34015



Strong fingers prevent unwanted breaking.

Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

Supplied with mounting holes to streamline installation.

Optional covers enhance protection and appearance.

Slotted Wall Wiring Duct, 3" x 4", Non-Adhesive, PVC, Gray, 7FT 70 ft/carton

Article Number 181-34015

Type SL3X4

Color Gray (GY)

Quantity Per carton

Product Description HellermannTyton Slotted Wall Wiring Duct features break-away fingers that provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly cut for joints and T's.

Short Description Slotted Wall Wiring Duct, 3" x 4", Non-Adhesive, PVC, Gray, 7FT 70 ft/carton

Global Part Name SL3X4-PVC-GY

Length L (Imperial) 7

Length L (Metric) 2.13

Fixation Method Non-Adhesive

Width W (Imperial) 3.00

Width W (Metric) 76.20

Height H (Imperial) 3.07

Height H (Metric) 77.90

Mounting Hole Centers (Imperial) 4.0

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability Self-extinguishing

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 70

Package Quantity (Metric) 21.3

Customs Number 3926909988