


## Specification Sheet

Part Number: 183-11050



Excellent fire-safety characteristics.

Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.

Halogen Free Slotted Wiring Duct, w/o Adhesive, 100mm x 50mm, PC/ABS, Gray RAL, 20 m/Box

Article Number	183-11050
Type	HTWD-HF-100X50
Color	Gray RAL 7035 (7035)
Quantity Per	box
Product Description	HellermannTyton HTWD-HF halogen-free ducts are used wherever there are high demands on personal or material safety, such as public transport, tunnels, escalators and data processing centers. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection. Base perforation according to DIN EN 50085. Note: Halogen-free PC+ABS is not resistant to all oils and greases.
Short Description	Halogen Free Slotted Wiring Duct, w/o Adhesive, 100mm x 50mm, PC/ABS, Gray RAL, 20 m/Box

Global Part Name	HTWD-HF-100X50-PC/ABS-GY
Length L (Imperial)	6.56
Length L (Metric)	2
Fixation Method	Screw Mounting
Width W (Imperial)	3.94
Width W (Metric)	100
Height H (Imperial)	1.97
Height H (Metric)	50.0
Material	Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)
Material Shortcut	PC/ABS
Flammability	UL 94 V-0
Halogen Free	Yes
Operating Temperature	-13°F to +194°F (-25°C to +90°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Certification/Specification	DIN EN [45545-2] UL   ANSI/UL 62275
UL Recognized (US)	Yes
Package Quantity (Imperial)	65.62
Package Quantity (Metric)	20
Customs Number	3925900000

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)