

Specification Sheet

Part Number: 183-13750



Excellent fire-safety characteristics.

Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.

Halogen Free Slotted Wiring Duct, w/o Adhesive, 37.5mm x 50mm, PC/ABS, Gray RAL, 32 m/Box

Article Number	183-13750
----------------	-----------

Type	HTWD-HF-37.5X50
------	-----------------

Color	Gray RAL 7035 (7035)
-------	----------------------

Quantity Per	box
--------------	-----

Product Description	HellermannTyton HTWD-HF halogen-free ducts are used wherever there are high demands on personal or material safety, such as public transport, tunnels, escalators and data processing centers. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection. Base perforation according to DIN EN 50085. Note: Halogen-free PC+ABS is not resistant to all oils and greases.
---------------------	--

Short Description	Halogen Free Slotted Wiring Duct, w/o Adhesive, 37.5mm x 50mm, PC/ABS, Gray RAL, 32 m/Box
-------------------	---

Global Part Name	HTWD-HF-37.5X50-PC/ABS-GY
Length L (Imperial)	6.56
Length L (Metric)	2
Fixation Method	Screw Mounting
Width W (Imperial)	1.48
Width W (Metric)	37.5
Height H (Imperial)	1.97
Height H (Metric)	50.0
Material	Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)
Material Shortcut	PC/ABS
Flammability	UL 94 V-0
Halogen Free	Yes
Operating Temperature	-13°F to +194°F (-25°C to +90°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Certification/Specification	DIN EN [45545-2] UL ANSI/UL 62275
UL Recognized (US)	Yes
Package Quantity (Imperial)	104.99
Package Quantity (Metric)	32
Customs Number	3925900000