

Specification Sheet


Part Number: 184-12009

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Gray, 7FT, 140ft/Carton

Article Number 184-12009

Type SLHD1X2

Color Gray (GY)

Quantity Per carton

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1" x 2", Non-Adhesive, PVC, Gray, 7FT, 140ft/Carton

Global Part Name SLHD1X2-PVC-GY

Length L (Imperial) 7

Length L (Metric) 2.13

Width W (Imperial) 1.00

Width W (Metric) 25.40

Height H (Imperial) 1.06

Height H (Metric) 26.92

Mounting Hole Centers (Imperial) 2.00

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability Self-extinguishing

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Certification/Specification CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 140.0

Package Quantity (Metric) 42.67

Customs Number 3925900000

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)