## **HellermannTyton**

## **Specification Sheet**

Part Number: 184-15102

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

High Density Slotted Wall Wiring Duct, 1.5" x 1", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	184-15102
Туре	SLHD1.5X1
Color	White (WH)
Quantity Per	carton
Product Description	HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
Short Description	High Density Slotted Wall Wiring Duct, 1.5" x 1", Non-Adhesive, PVC, White, 120ft/Carton



**Global Part Name** 

Length L (Imperial)	6.0	
Length L (Metric)	1.83	
Fixation Method	Non-Adhesive	
Width W (Imperial)	1.5	
Width W (Metric)	38.1	
Height H (Imperial)	1.06	
Height H (Metric)	26.9	
Mounting Hole Centers (Imperial)	2.0	

Material	Polyvinylchloride (PVC)	
Material Shortcut	PVC	
Flammability	Self-extinguishing	
Halogen Free	No	
Operating Temperature	+122°F (+50°C)	

Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	UL EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 CSA
UL Recognized (US)	Yes
Package Quantity (Imperial)	120.0
Package Quantity (Metric)	36.58
Customs Number	3925900000

© 2023 HellermannTyton. All Rights Reserved.			
Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions