

Specification Sheet

Part Number: 184-15404

Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.

Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.

Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.

Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.



High Density Slotted Wall Wiring Duct, 1.5" x 4", Non-Adhesive, PVC, White, 7FT, 140ft/Carton

Article Number 184-15404

Type SLHD1.5X4

Color White (WH)

Quantity Per carton

Product Description HellermannTyton High-Density Slotted Wall Wiring Duct features

narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and

components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1.5" x 4", Non-Adhesive, PVC,

White, 7FT, 140ft/Carton

Global	Dort	NIOMO
CHODAL	Pan	Name

SLHD1.5X4-PVC-WH

Length L (Imperial)	7
Length L (Metric)	2.13
Width W (Imperial)	1.50
Width W (Metric)	38.10
Height H (Imperial)	1.57
Height H (Metric)	39.9
Mounting Hole Centers (Imperial)	2.00
NA 4 1 1	Dalaria dalah lari da (D)(O)

Material Shortcut PVC

Flammability Self-extinguishing

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Certification/Specification

UL CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A

UL Recognized (US)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity (Imperial)

140.0

Package Quantity (Metric)

42.67

3925900000

© 2023 HellermannTyton. All Rights Reserved.

Customs Number

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions