HellermannTyton

Specification Sheet

Part Number: SNP12A10M4

Installation and removal can be five times faster

than conventional clamps.

Heat stabilized material is suitable for high temperature applications.

Completely reusable.

Will not rust or corrode.

Safety engineered.

No protruding band or cluster.

Can be installed with hose in place.

One-hand installation for tight places.



Snapper Hose Clamp, 0.61 - 0.72" Bundle Diameter, POM, White, 1000/pkg

Article Number 190-00253

Type SNP12A

Color White (WH)

Quantity Per bag

Product Description	The Snapper Hose Clamp features a ratchet-style closure for reduced assembly time. It can be added after connection of the hose. Release by sliding the ratchet ends apart. These white polyacetal Snappers can be used in under-hood applications and are stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils and greases. Custom design and color options are available based upon application and volume requirements.
Short Description	Snapper Hose Clamp, 0.61 - 0.72" Bundle Diameter, POM, White, 1000/pkg
Global Part Name	SNP12A-POM-WH
Fixation Method	Plug-in mounting
Variant	Closed
Bundle Diameter Min (Imperial)	0.66
Bundle Diameter Min (Metric)	16.8
Bundle Diameter Max (Imperial)	0.72
Bundle Diameter Max (Metric)	18.4

Material

Wall Thickness WT (Imperial)

Wall Thickness WT (Metric)

Polyacetal (POM)

.070

1.78

Material Shortcut POM

Flammability UL 94 HB

UV Resistant (Yes/No) No

Use Conditions For Indoor and Outdoor Use

Operating Temperature -40°F to +194°F (-40°C to +90°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988

© 2025 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions