HellermannTyton

Specification Sheet

Part Number: SNP2GHS0C2

Installation and removal can be five times faster

than conventional clamps.

Heat stabilized material is suitable for high temperature applications.

Completely reusable.

Will not rust or corrode.

Safety engineered.

No protruding band or cluster.

Can be installed with hose in place.

One-hand installation for tight places.



Article Number

192-10020

Type

SNP2

Color

Black (BK)

Quantity Per

bag

Product Description	The Snapper Hose Clamp features a ratchet-style closure for reduced assembly time. It can be added after connection of the hose. Release by sliding the ratchet ends apart. Snappers can be used in under-hood applications and are stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils and greases. They are manufactured in black PA66 glass filled, impact modified, heat stabilized material. Custom design and color options are available based upon application and volume requirements.
Short Description	Snapper Hose Clamp, 0.37" - 0.41" Bundle Diameter, PA66GF13, Black, 100/pkg
Global Part Name	SNP2-PA66GF13-BK
Fixation Method	Plug-in mounting
Variant	Closed
Width W (Metric)	17.6
Bundle Diameter Min (Imperial)	0.37
Bundle Diameter Min (Metric)	9.3
Bundle Diameter Max (Imperial)	0.41
Bundle Diameter Max (Metric)	10.5

0.44

10

0.068

Nominal Diameter (Imperial)

Nominal Diameter (Metric)

Wall Thickness WT (Imperial)

Material Polyamide 6.6 glass filled impact modified heat stabilized

(PA66GF13%)

Material Shortcut PA66GF13

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988