

Specification Sheet

Part Number: 1P9C



Sheathing allows flexible routing and lead-out of cables.
The inner edges are beveled preventing damage to cables.

Sheathing is reusable and resistant to most chemicals.

Spiralwrap is UL Recognized.

Spiralwrap Protective Sheathing, 0.13" Diameter, PTFE, Natural, 100 ft/roll

Article Number 161-05015

Type 1P

Color Natural (NA)

Quantity Per reel

Product Description HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize. Polytetrafluoroethylene-Teflon (PTFE) offers the widest operating temperature range of any material. It's chemically inert and nonflammable. Natural color is milky white. Available by special order in black and colors.

Short Description Spiralwrap Protective Sheathing, 0.13" Diameter, PTFE, Natural, 100 ft/roll

Global Part Name	1P-PTFE-NA
Length L (Imperial)	100.0
Length L (Metric)	30.48
Variant	Spiral Binding
Bundle Diameter Min (Imperial)	0.0625
Bundle Diameter Min (Metric)	1.6
Bundle Diameter Max (Imperial)	0.5
Bundle Diameter Max (Metric)	12.7
Diameter D (Imperial)	0.125
Diameter D (Metric)	3.18
Nominal Diameter (Imperial)	0.13
Nominal Diameter (Metric)	3.18
Wall Thickness WT (Imperial)	.020
Wall Thickness WT (Metric)	0.51

Material	Polytetrafluoroethylene (PTFE)
Material Shortcut	PTFE
Flammability	Non-flammable
Halogen Free	No
Operating Temperature	-449°F to +500°F (-267°C to +260°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	3926909988