

## Specification Sheet

Part Number: TSRP3FW-8A

Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick re-entry as well as providing a secure installation of power cables.

U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards.

Manufactured from UL 94V-0 rated PVC material.

Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.

Large base for greater adhesive surface.

Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface.

Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking.

Junction boxes can be used for electrical or data outlets.

Designed to complement HellermannTyton's industry standard TSR low voltage raceway system.



One Piece Power Rated Raceway, 1-3/4", 8.0 ft Long, PVC, Office White, 160ft/Carton

|                |           |
|----------------|-----------|
| Article Number | 250-63800 |
|----------------|-----------|

|      |          |
|------|----------|
| Type | TSRP3-8A |
|------|----------|

|       |                     |
|-------|---------------------|
| Color | Office White (OEWH) |
|-------|---------------------|

|                     |  |
|---------------------|--|
| Quantity Per        | carton   |
| Product Description | HellermannTyton's TSRP power surface raceway is a one piece, non-metallic, adhesive backed latching raceway designed to aesthetically organize and route either power or communications cables. Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick reentry as well as providing a secure installation of power cables. |
| Short Description   | One Piece Power Rated Raceway, 1-3/4", 8.0 ft Long, PVC, Office White, 160ft/Carton  |
| Global Part Name    | TSRP3-8A-PVC-WH  |
| Length L (Imperial) | 8.0  |
| Length L (Metric)   | 2.44   |
| Width W (Imperial)  | 1.75   |
| Width W (Metric)    | 44.45  |
| Height H (Imperial) | 1.0  |
| Height H (Metric)   | 25.40  |
| Material            | Polyvinylchloride (PVC)  |
| Material Shortcut   | PVC  |
| Flammability        | UL 94 V-0  |

|                              |                     |
|------------------------------|---------------------|
| Halogen Free                 | No                  |
| UV Resistant (Yes/No)        | No                  |
| Use Conditions               | For Indoor Use Only |
| Operating Temperature        | +122°F (+50°C)      |
| Reach Compliant (Article 33) | No                  |
| ROHS Compliant               | Yes                 |
| UL Listed (US and Canada)    | Yes                 |
| UL Listed (US)               | Yes                 |
| Package Quantity (Imperial)  | 160.0               |
| Package Quantity (Metric)    | 48.80               |
| Customs Number               | 3925900000          |