

Specification Sheet

Part Number: 300-30957



Tubing is 2:1, thin wall that provides protection against corrosion and mechanical abrasion.

Available in multiple colors and sizes for easy marking and handling.

Conveniently stored in a handy dispenser box for quick and easy use.

Article Number	300-30957
Type	HIS-PACK-9.5/4.7
Color	Green-Yellow (GNYE)
Quantity Per	box
Product Description	HIS-PACK Heat Shrink is a general-purpose, thin-wall Polyolefin tubing that provides electrical insulation and protection against corrosion and mechanical abrasion. HIS-PACKs are available in multiple colors and ten sizes ranging from 1/16" (1.2mm) to 1" (25.4mm). Tubing is conveniently stored in a handy dispenser box with hang tag and is RoHS approved.
Short Description	Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, 0.37 Supp/.17" Recov Dia, PO-X, Grn/Yel, 16.4ft/pkg

Global Part Name	HIS-PACK-9.5/4.7-PO-X-GNYE
Length L (Imperial)	16.4
Length L (Metric)	5.0
Variant	Thin-Wall
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	6.4
Wall Thickness WT (Imperial)	.023
Wall Thickness WT (Metric)	0.60
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Flammability	UL 224 VW-1 (except clear) Self-extinguishing (except for transparent)
Halogen Free	No
UV Resistant (Yes/No)	No
Operating Temperature	-67°F to +257°F (-55°C to +125°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL ANSI/UL 224 UL CSA-C22.1 UL CSA-C22.2 No.198.1
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	16.4
Package Quantity (Metric)	5
Customs Number	3926909988
Weight (Metric)	0.181
Weight (Imperial)	0.4