

## Specification Sheet

Part Number: 321-30100

High shrink-ratio heavy-duty heat shrinkable tubing designed to pass over large size connectors and shrink down onto much smaller cable jackets. The thermoplastic adhesive lined tubing provides environmental sealing, excellent insulation and resistance to impact and abrasion.

The 6:1 shrink-ratio conforms well to highly variable substrate dimensions and simplifies cable repair.



Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 6:1, 1.25", 33/5.5 dia, PO, Black, 3/pkg

|                |               |
|----------------|---------------|
| Article Number | 321-30100     |
| Type           | HA67-33.0/5.5 |
| Color          | Black (BK)    |
| Quantity Per   | pcs.          |

|                     |   |
|---------------------|---|
| Product Description | HA47 is a thick-wall adhesive lined heat shrink tubing for use in applications up to 1000 volts. The adhesive lining provides excellent moisture sealing and weather protection, making it suitable for above and below ground applications. Made of a polyolefin outer material, this tubing has a shrink ratio up to 3.5 to 1. The adhesive lining begins to activate as the temperature approaches 185° F (85° C). |
|---------------------|---|

|                   |  |
|-------------------|--|
| Short Description | Heat Shrink Tubing, 4' Long Stick, Thick Wall Adhesive Lined, Up to 6:1, 1.25", 33/5.5 dia, PO, Black, 3/pkg |
|-------------------|--|

|                             |                                 |
|-----------------------------|---------------------------------|
| Global Part Name            | HA67-33.0/5.5-PO-X-BK           |
| Length L (Imperial)         | 4                               |
| Length L (Metric)           | 1.2                             |
| Voltage Range               | Low Voltage , up to 1,000 Volt  |
| Variant                     | Thick-Wall                      |
| Diameter D (Imperial)       | 1.25                            |
| Diameter D (Metric)         | 33.0                            |
| Nominal Diameter (Imperial) | 1.25                            |
| Nominal Diameter (Metric)   | 33.0                            |
| Wall Thickness WT (Metric)  | 3.4                             |
| Material                    | Polyolefin, cross-linked (PO-X) |
| Material Shortcut           | PO-X                            |
| Adhesive                    | Hot melt adhesive               |
| Flammability                | Not flame retardant             |

|                              |                                   |
|------------------------------|-----------------------------------|
| Halogen Free                 | Yes                               |
| UV Resistant (Yes/No)        | No                                |
| Operating Temperature        | -67°F to +230°F (-55°C to +110°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 3                                 |
| Package Quantity (Metric)    | 3                                 |
| Customs Number               | 3926909988                        |