

Specification Sheet

Part Number: 553-50035

Slide Slit and optional center slits for easy wire insertion.
Smooth surface for clean and legible printing.

Supplied on a ladder style carrier so that markers can be kitted after printing.

A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.



ShrinkTrak Labels, 1-Sided, 1-Slit, 0.75" (19.05mm), PO-X, White, 500/box

Article Number 553-50035

Type HST18-6WH-S

Color White (WH)

Quantity Per box

Product Description HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description ShrinkTrak Labels, 1-Sided, 1-Slit, 0.75" (19.05mm), PO-X, White, 500/box

Global Part Name HST18-6WH-S-PO-X-WH

Variant Thin-Wall

Width W (Imperial) 0.95

Width W (Metric) 24.13

Thickness T (Imperial) .003

Thickness T (Metric) .0762

Height H (Imperial) 1.2

Height H (Metric) 30.48

Width of Liner (Metric) 76.2

Width of Liner (Imperial) 3.0

Outside Diameter OD (Imperial) 0.75

Outside Diameter OD (Metric) 19.05

Outside Diameter Max (Imperial) 0.75

Outside Diameter Max (Metric) 19.05

Wall Thickness WT (Imperial) 0.036

Wall Thickness WT (Metric) 0.914

| | |
|------------------------------|--|
| Material | Polyolefin, cross-linked (PO-X) |
| Material Shortcut | PO-X |
| US MIL SPEC | SAE-AMS-DTL-23053/5 Class 1 and 3 MIL-STD-202G Method 215K SAE-AS81531 |
| Flammability | UL 224 VW-1 |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -67°F to +275°F (-55°C to +135°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL 224 125 °C 600V VW-1 |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3917320000 |
| Labels per Column | 1 |

