

Specification Sheet

Part Number: 558-00503

Continuous Polyester Labels are made with UV stable materials for long outdoor life.

Labels use UV stable permanent ink.

Continuous polyester is provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems.



Adhesive Labels, Solid Color Continuous Roll, 3.0" x 100', UV Stable PET, Red, 100 ft/roll

| | |
|----------------|------------|
| Article Number | 558-00503 |
| Type | HT3RDHB250 |
| Color | Red (RD) |
| Quantity Per | roll |

Product Description Colored continuous rolls offer a high bond adhesive that is sustainable for low surface energy substrates such as the low density plastics on the front of an inverter or powder coat paint surfaces. The adhesive is designed to adhere to textured surfaces without peeling or falling off.

Short Description Adhesive Labels, Solid Color Continuous Roll, 3.0" x 100', UV Stable PET, Red, 100 ft/roll

| | |
|--------------------------------|--|
| Global Part Name | HT3RDHB250-840/281-RD |
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.48 |
| Variant | 3.2mil, 50lb bleached kraft paper |
| Width W (Imperial) | 3.0 |
| Width W (Metric) | 76.2 |
| Width of Liner (Metric) | 76.2 |
| Width of Liner (Imperial) | 3.0 |
| Material | Type 840/281, Polyester, UV-stabilised, clear polyester laminate (840/281) |
| Material Shortcut | 840/281 |
| Adhesive | Acrylic |
| Halogen Free | No |
| UV Resistant (Yes/No) | Yes |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |

| | |
|------------------------------|---|
| Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL 969 NEC2011 ANSI Standard Z535.4 IFC 2012 CSA 66956 NEC2014 |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 30.48 |
| Customs Number | 3919102055 |
| Labels per Column | 1 |
| Labels per Row | 1 |