

Specification Sheet

Part Number: RO512

Compact to easily fit in a pocket or on a tool belt.

Dispenser can be reloaded over and over, making it cost-effective to use.

Dispenser edge allows easy removal of label liner.

Dispenser protects labels from dirt and moisture before use, extending the life and quality of the labels.



Article Number 590-05120

Type RO512

Color White (WH) Clear (CL)

Quantity Per EA

Product Description HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

Short Description Rite-On Self-Laminating Label Dispenser, 0.75 x 0.5 x 1.875", VL, White, 150/roll

Global Part Name	RO512-100B-CL/WH
------------------	------------------

Fixation Method	Pasting / Stick
-----------------	-----------------

Variant	Roller form
---------	-------------

Width W (Imperial)	0.75
--------------------	------

Width W (Metric)	19.05
------------------	-------

Bundle Diameter Min (Imperial)	0.26
--------------------------------	------

Bundle Diameter Min (Metric)	6.68
------------------------------	------

Bundle Diameter Max (Imperial)	0.33
--------------------------------	------

Bundle Diameter Max (Metric)	8.38
------------------------------	------

Height H (Imperial)	0.50
---------------------	------

Height H (Metric)	12.7
-------------------	------

Outside Diameter Max (Imperial)	0.33
---------------------------------	------

Outside Diameter Min (Metric)	6.68
-------------------------------	------

Outside Diameter Min (Imperial)	0.263
---------------------------------	-------

Outside Diameter Max (Metric)	8.38
-------------------------------	------

Material	Type 100B, Vinyl, white transparent, self-laminating (100B)
Material Shortcut	100B
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	No
Adhesive Operating Temperature	-40°F to +176°F (-40°C to +80°C)
Operating Temperature	-40°F to +176°F (-40°C to +80°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	150
Package Quantity (Metric)	150
Customs Number	3919102055

