

## Specification Sheet

Part Number: TAG51L-105

Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.

The material is 1.0 mil thick, allowing it to conform around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.



|                |           |
|----------------|-----------|
| Article Number | 594-51105 |
|----------------|-----------|

|      |        |
|------|--------|
| Type | TAG51L |
|------|--------|

|       |            |
|-------|------------|
| Color | White (WH) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification. |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                          |
|-------------------|------------------------------------------------------------------------------------------|
| Short Description | Laser Tag Label, Self-Laminating, 1.0" x .35" x .75", 84 Per Sheet, PET, White, 5000/pkg |
|-------------------|------------------------------------------------------------------------------------------|

|                                 |                                  |
|---------------------------------|----------------------------------|
| Global Part Name                | TAG51L-105-WH                    |
| Width W (Imperial)              | 1.0                              |
| Width W (Metric)                | 25.4                             |
| Bundle Diameter Min (Imperial)  | 0.11                             |
| Bundle Diameter Min (Metric)    | 2.79                             |
| Bundle Diameter Max (Imperial)  | 0.12                             |
| Bundle Diameter Max (Metric)    | 3.17                             |
| Thickness T (Metric)            | 35.0                             |
| Width of Liner (Metric)         | 215.00                           |
| Width of Liner (Imperial)       | 8.5                              |
| Outside Diameter Max (Imperial) | 0.129                            |
| Outside Diameter Min (Metric)   | 1.6                              |
| Outside Diameter Min (Imperial) | 0.059                            |
| Outside Diameter Max (Metric)   | 3.30                             |
| Material                        | Type 105, Polyester, white (105) |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Material Shortcut              | 105                               |
| Adhesive                       | Acrylic                           |
| Halogen Free                   | No                                |
| UV Resistant (Yes/No)          | No                                |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature          | -40°F to +300°F (-40°C to +149°C) |
| Reach Compliant (Article 33)   | Yes                               |
| ROHS Compliant                 | Yes                               |
| Package Quantity (Imperial)    | 5000                              |
| Package Quantity (Metric)      | 5000                              |
| Customs Number                 | 3919905060                        |
| Labels per Column              | 12                                |
| Labels per Row                 | 8                                 |