

## Specification Sheet

Part Number: 596-00203

Pre-printed solar labels are made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.



High abrasion and scuff resistance for high performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-Printed Header Label, DANGER, 6.0" x 4.0", PET, Red, 250/roll

Article Number	596-00203
Type	4X6DANGER
Color	Red (RD)
Quantity Per	roll
Product Description	HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Pre-Printed Header Label, DANGER, 6.0" x 4.0", PET, Red, 250/roll
Global Part Name	4X6DANGER-336/926-RD
Width W (Imperial)	6.0
Width W (Metric)	152.4
Thickness T (Metric)	64.0
Height H (Imperial)	4.0
Height H (Metric)	101.6
Width of Liner (Metric)	106.6
Width of Liner (Imperial)	4.2
Material	Type 336/926, Polyester, UV-stabilized, clear polyester laminate (336/926)
Material Shortcut	336/926
Adhesive	Acrylic
Halogen Free	Yes
UV Resistant (Yes/No)	Yes

Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2011 NEC2017 NEC2014 NEC2020
UL Recognized (US)	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	250
Customs Number	3919102055
Labels per Column	1
Labels per Row	1