

Specification Sheet

Part Number: 596-00751



Made with UV stable inks and materials for durability and weather resistance.
The labels are supplied with aggressive adhesive to ensure long life.
Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, SOLAR SYSTEM BREAKER, 2.0" x 1.0", VL, Red, 50/roll

Article Number	596-00751
Type	SSB
Color	Red (RD)
Quantity Per	roll
Product Description	Many times common solar label designs are specified even though they might not be required by code. HellermannTyton offers a selection of some of the most commonly requested labels for use on solar installations.
Short Description	Solar Label, SOLAR SYSTEM BREAKER, 2.0" x 1.0", VL, Red, 50/roll
Global Part Name	SSB-V-RD

Width W (Imperial)	2.0
Width W (Metric)	50.8
Height H (Imperial)	1.0
Height H (Metric)	25.40
Material	Vinyl (V)
Material Shortcut	V
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2014 NEC2020 NEC2017 NEC2011

Warranty (US)	Yes
---------------	-----

UL Recognized (US)	Yes
--------------------	-----

Package Quantity (Imperial)	50
-----------------------------	----

Package Quantity (Metric)	50
---------------------------	----

Customs Number	3919102055
----------------	------------

Labels per Column	1
-------------------	---

Labels per Row	1
----------------	---