

## Specification Sheet

Part Number: 596-00853

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high-performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.



Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 10/pkg

|                |           |
|----------------|-----------|
| Article Number | 596-00853 |
| Type           | ACDISCT10 |
| Color          | Red (RD)  |
| Quantity Per   | pack      |

|                        |   |
|------------------------|---|
| Product Description    | HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack. |
| Short Description      | Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 10/pkg  |
| Global Part Name       | ACDISCT10-840/281-RD  |
| Local Order Number 2   | Cross Reference = 50 per roll: 596-00237; Printable Metal Solar Placard 5 pack: 596-00841; Engravable Metal Solar Placard 5 pack: 596-00857; Spanish version 50 per roll: 596-00813   |
| Width W (Imperial)     | 3.75  |
| Width W (Metric)       | 92.25   |
| Thickness T (Imperial) | 0.0025  |
| Thickness T (Metric)   | 64.0  |
| Height H (Imperial)    | 1.0   |
| Height H (Metric)      | 25.40   |

|                                |  |
|--------------------------------|--|
| Material                       | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| Material Shortcut              | 840/281  |
| Adhesive                       | Acrylic  |
| Halogen Free                   | Yes  |
| UV Resistant (Yes/No)          | Yes  |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C)  |
| Operating Temperature          | -40°F to +302°F (-40°C to +150°C)  |
| Reach Compliant (Article 33)   | Yes  |
| ROHS Compliant                 | Yes  |
| Certification/Specification    | UL 969 CSA 66956 NEC2017 NEC2014 NEC2020 NEC2011 NEC2023                   |
| Warranty (US)                  | Yes  |
| UL Recognized (US)             | Yes  |
| Package Quantity (Imperial)    | 10   |
| Package Quantity (Metric)      | 10   |
| Customs Number                 | 3919905060   |

Labels per Column 1

Labels per Row 1

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)