

## Specification Sheet

Part Number: 596-01006

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

Abrasion resistant for high-performance identification.

Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.



Solar Label, SOLAR PV DC CIRCUIT LABEL, 6.5" X 1.0", VL, Red, 10/pkg

|                |              |
|----------------|--------------|
| Article Number | 596-01006    |
| Type           | SPVDCC202010 |
| Color          | Red (RD)     |
| Quantity Per   | pack         |

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description       | HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack. |
| Short Description         | Solar Label, SOLAR PV DC CIRCUIT LABEL, 6.5" X 1.0", VL, Red, 10/pkg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Global Part Name          | SPVDCC202010-443/281-RD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Width W (Imperial)        | 6.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Width W (Metric)          | 165.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Thickness T (Imperial)    | 0.0025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Thickness T (Metric)      | 64.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Height H (Imperial)       | 1.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Height H (Metric)         | 25.40                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Width of Liner (Metric)   | 28.57                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Width of Liner (Imperial) | 1.125                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                |                                                                                           |
|--------------------------------|-------------------------------------------------------------------------------------------|
| Material                       | Type 443/281, UV-stabilised, flexible white vinyl with clear polyester laminate (443/281) |
| Material Shortcut              | 443/281                                                                                   |
| Adhesive                       | Acrylic                                                                                   |
| Halogen Free                   | No                                                                                        |
| UV Resistant (Yes/No)          | Yes                                                                                       |
| Adhesive Operating Temperature | -40°F to +174°F (-40°C to +79°C)                                                          |
| Operating Temperature          | -40°F to +174°F (-40°C to +79°C)                                                          |
| Reach Compliant (Article 33)   | Yes                                                                                       |
| ROHS Compliant                 | Yes                                                                                       |
| Certification/Specification    | UL 969 NEC2020                                                                            |
| UL Recognized (US)             | Yes                                                                                       |
| Package Quantity (Imperial)    | 10                                                                                        |
| Package Quantity (Metric)      | 10                                                                                        |
| Customs Number                 | 3919905060                                                                                |
| Labels per Column              | 1                                                                                         |

