

Specification Sheet

Part Number: TYHCT-250

Handi-Cards have a split backing so that a portion of the liner can be removed to expose the markers for easy dispensing.

Handi-Cards are kitted on the card so that specific markers can be removed without affecting the other markers on the card.

Markers are pre-printed so no additional post printing is required, saving time and money.

Label material is a conformable cloth that ensures markers stay on wires and cables for the life of the application.



Handi-Card Wire and Cable Markers, 0.25" x 1.5", 16 Across, Cloth, White, 5000/pkg

Article Number	598-00277
Type	TYHCT-250
Color	White (WH)
Quantity Per	reel
Product Description	HellermannTyton Handi-Card cloth label in the same format as standard Handi-Card labels but thermal transfer printable. Handi-Card labels are easy release pre-printed cloth markers, on a plastic card, with a strong adhesive for a long lasting bond on wire and cable.

Short Description	Handi-Card Wire and Cable Markers, 0.25" x 1.5", 16 Across, Cloth, White, 5000/pkg
Global Part Name	TYHCT-250-TYHC-WH
Length L (Imperial)	1.5
Length L (Metric)	38.1
Width W (Imperial)	0.25
Width W (Metric)	6.35
Bundle Diameter Min (Imperial)	0.13
Bundle Diameter Min (Metric)	3.40
Bundle Diameter Max (Imperial)	0.3
Bundle Diameter Max (Metric)	7.50
Thickness T (Metric)	35.0
Height H (Imperial)	1.5
Height H (Metric)	38.10
Width of Liner (Metric)	104.70
Width of Liner (Imperial)	4.12
Outside Diameter Max (Imperial)	0.29

Outside Diameter Min (Metric)	3.40
Outside Diameter Min (Imperial)	0.13
Outside Diameter Max (Metric)	7.50
Material	Vinyl Cloth (TYHC)
Material Shortcut	TYHC
Adhesive	Rubber
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Adhesive Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000

Customs Number 3919102055

Labels per Column 1

Labels per Row 16