

Specification Sheet

Part Number: ATS10266110

The ATS3080 cable tie is designed for optimized material utilization by using an innovative two-piece system consisting of individual strap and closures.

Waste-free cable tie system eliminates down time due to cleaning and opening waster containers.

Bundle diameter is mechanically detected and allows a flush cut off of the strap.

Available in reels of 1640 feet of strap and 5,000 closures.



Cable Ties for ATS3080, 50lb Tensile Strength, PA66HIRHSUV, Black, 1640 ft/reel

Article Number	102-66110
Type	Strap Black ATS3080
Color	Black (BK)
Quantity Per	reel
Product Description	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
Short Description	Cable Ties for ATS3080, 50lb Tensile Strength, PA66HIRHSUV, Black, 1640 ft/reel

Global Part Name Strap Black ATS3080-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 1640.0

Length L (Metric) 500.0

Identification Plate Position none

Reel Diameter (Imperial) 15.25

Reel Diameter (Metric) 387

Reel Width (Imperial) 3.5

Reel Width (Metric) 88.9

Releasable Closure No

Variant on reel

Width W (Imperial) 0.18

Width W (Metric) 4.5

Bundle Diameter Min (Metric) 0.0

Bundle Diameter Max (Imperial) 3.14

Bundle Diameter Max (Metric)	100
Height H (Imperial)	0.047
Height H (Metric)	1.2
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +203°F (-40°C to +95°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1640.0
Package Quantity (Metric)	500.0
Customs Number	3926909988
Reel Weight (Imperial)	6

