

Specification Sheet

Part Number: CTP1120STDUNSLI

Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.

Tubing provides full coverage where spiral wrap or other coverings may not be suitable.



Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat and cold on cables and wires.

Convoluted Tubing, Unslit, 1.5" Dia, PE, Black, 100 ft/ctn

Article Number 169-60540

Type CTP1120UNSLIT

Color Black (BK)

Quantity Per carton

Product Description

HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description	Convuluted Tubing, Unslit, 1.5" Dia, PE, Black, 100 ft/ctn
Global Part Name	CTP1120UNSLIT-PE-BK
Length L (Imperial)	100.0
Length L (Metric)	30.5
Variant	Unslit
Inner Diameter D (Imperial)	1.647
Inner Diameter D (Metric)	41.83
Diameter D (Imperial)	1.947
Diameter D (Metric)	49.45
Outside Diameter OD (Imperial)	1.947
Outside Diameter OD (Metric)	49.45
Nominal Diameter (Imperial)	1.5
Nominal Diameter (Metric)	38.1
Wall Thickness WT (Imperial)	0.006
Wall Thickness WT (Metric)	0.152

Material	Polyethylene (PE)
Material Shortcut	PE
Flammability	Not flame retardant
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	3926909988