

Specification Sheet

Part Number: FHF



Can be cut to length with scissors, eliminating waste and keeping stock to a minimum.

Available in 9 sizes, for thicknesses from .016" to .512", insuring proper fit.

Grommet, Panel Thickness 0.256"-0.319", PA6, Natural, 82ft/pkg

Article Number 251-21609

Type G51NF

Color Natural (NA)

Quantity Per reel

Product Description HellermannTyton's Flexiform grommet is a unique, continuous wire protection product which fits easily in all shapes and sizes of holes without the aid of tools or adhesives. Flexiform grommet can be used on any type of material including wood, steel, aluminum, plexiglass, and glass.

Short Description Grommet, Panel Thickness 0.256"-0.319", PA6, Natural, 82ft/pkg

Global Part Name G51NF-PA6-NA

| | |
|--------------------------------|-------------------|
| Length L (Imperial) | 82.0 |
| Variant | Open |
| Width W (Imperial) | 0.449 |
| Width W (Metric) | 11.4 |
| Height H (Imperial) | 0.268 |
| Height H (Metric) | 6.8 |
| Panel Thickness Min (Imperial) | 0.256 |
| Panel Thickness Max (Imperial) | 0.319 |
| Panel Thickness Min (Metric) | 6.50 |
| Panel Thickness Max (Metric) | 8.10 |
| Material | Polyamide 6 (PA6) |
| Material Shortcut | PA6 |
| US MIL SPEC | MS21266-6N |
| Flammability | UL 94 HB |

| | |
|------------------------------|----------------------------------|
| Halogen Free | Yes |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -76°F to +203°F (-60°C to +95°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | NASM21266 |
| Package Quantity (Imperial) | 82 |
| Package Quantity (Metric) | 25 |
| Customs Number | 3926909988 |