


Specification Sheet

Part Number: FSU20-M20-C

Nickel plated brass compression fitting used with FSU, LFHU and FPU flexible metallic conduit.

Fitting includes elastomeric sealing washer for IP65 ingress protection.

Suitable for knockouts or NPT / Metric threaded entries as fitting rotates until tightened.



Metallic Compression Fitting, Straight, M20 Metric Thread, 1/2" (20mm) Dia, NPB Metal, 10/pkg

Article Number	166-90540
Type	FSU20-M20-C
Color	Metal (ML)
Quantity Per	pack
Product Description	Multipart straight compression fitting with fixed external thread pattern suitable for threaded or knockout entries. Constructed with nickel plated brass components that resist corrosion, ensures high mechanical strength and electrical continuity. Fitting comprised of body, nut, grounding ferrule and nylon compression seal. For use with FSU, FPU, and LFHU flexible metal conduits.
Short Description	Metallic Compression Fitting, Straight, M20 Metric Thread, 1/2" (20mm) Dia, NPB Metal, 10/pkg

Global Part Name	FSU20-M20-C-NPB/PA6-ML
Length L (Imperial)	1.32
Length L (Metric)	33.5
Variant	Straight
Height H (Imperial)	0.85
Height H (Metric)	26.0
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	20.0
Material	Polyamide 6 (PA6) Nickel Plated Brass (NPB)
Material Shortcut	NPB PA6
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-58°F to +275°F (-50°C to +135°C)
Reach Compliant (Article 33)	Yes

ROHS Compliant	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	7412200000