

## Specification Sheet

Part Number: FU16-M16-M



Nickel plated brass compression fitting used with FU-x series flexible metallic conduit.

Two part fitting comprised of shell and body with external metric thread delivers IP40 ingress protection.

Suitable for knockouts and secured with a metric threaded locknut.

Metallic Compression Fitting, Fixed Straight, M16 Metric Thread, 3/8" (16mm) Dia, NPB Metal, 10/pkg

Article Number 166-90762

Type FU16-M16-M

Color Metal (ML)

Quantity Per pack

Product Description Two-part nickel plated brass straight fitting with fixed external metric thread. Fitting comprised of shell and body suitable for knockout entries. For use with FU-x flexible metal conduit.

Short Description Metallic Compression Fitting, Fixed Straight, M16 Metric Thread, 3/8" (16mm) Dia, NPB Metal, 10/pkg

Global Part Name FU16-M16-M-NPB-ML

Length L (Imperial)	0.98
Length L (Metric)	25.0
Variant	Straight
Height H (Imperial)	0.79
Height H (Metric)	20.0
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	16.0
Material	Nickel Plated Brass (NPB)
Material Shortcut	NPB
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-58°F to +572°F (-50°C to +300°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

Customs Number 7412200000