

Specification Sheet

Part Number: ISO4X250H1



Design provides quick and easy assembly.

Isolator mount dampens harmful vibrations on bundles

Material is durable, chemical and abrasion resistant, and remains flexible in low temperatures.

Isolator Mount for separating 0.25" Tubing, 0.25" Max Bundle Diameter, TPV, Black, 500/pkg

Article Number 151-00455

Type ISO4X250

Color Black (BK)

Quantity Per carton

Product Description HellermannTyton's isolator mount is used to align and separate 1/4" tubing or brake lines. Easy to assemble, the isolator dampens vibrations and can be used with up to four brake lines. Mounting the isolator can be accomplished with HellermannTyton's standard cable ties, button head ties, and any of HellermannTyton's heavy equipment mounts. Mounting is optional, but recommended for long runs. The isolator is durable, chemical and abrasion resistant, and remains flexible in low temperatures.

Short Description	Isolator Mount for separating 0.25" Tubing, 0.25" Max Bundle Diameter, TPV, Black, 500/pkg
Global Part Name	ISO4X250-TPV-BK
Length L (Metric)	23.4
Width W (Imperial)	0.92
Width W (Metric)	23.4
Height H (Imperial)	1.36
Height H (Metric)	34.5
Cable Tie Width Max (Imperial)	0.52
Cable Tie Width Max (Metric)	13.2
Material	Thermoplastic vulcanized (TPV) rubber
Material Shortcut	TPV
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Operating Temperature	-110°F to +347°F (-79°C to +175°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988