
Array Technologies Ratchet Clamp

Features and Benefits

- One-piece ratchet clamp can be pre-installed on the torque tube, even prior to arrival of modules and wire harnesses onsite.
- Quick, toolless, one-handed installation is easier and safer for installers.
- Releasable and re-closeable clamp allows for adjusting or adding wires.
- Plastic construction won't cut or chafe wires.
- Clamp saddle provides additional routing option using a cable tie, eliminating the need to drill or add complex routing parts.
- Impact modified, heat and UV stabilized PA66 provides long-term durability in extreme environments.
- ATI-specific stainless steel mounting clip designed to last through severe weather and single axis tracker movement.



Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV), Stainless Steel (SS304)		
Color	Black (BK)		
Operating Temperature	-40°F to +221°F (-40°C to +105°C)		



PART NO.	ТҮРЕ	Min. Bundle Diameter in. (mm)	Max. Bundle Diameter in. (mm)	Fixation Method	Width (W) in. (mm)	Pkg. Qty.
156-04196	IRCBATI	0.5 (12.7)	0.8 (19.6)	Mounting Hanger	1.4 (34.8)	200

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

Contact HellermannTyton for more information. Visit **www.hellermann.tyton.com** or call **800.537.1512**

Disclaimer: The information in this datasheet is for informational purposes only. Information is subject to change at any time without notice.

TECHNICAL DATA SHEET

HellermannTyton