

Specification Sheet

Part Number: MMB.50M4



Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces. The mounts have easy installation into predrilled holes allowing for faster use.

Masonry Cable Tie Mount, 1.24"L, 0.25" Hole Dia, 0.18" Max Cable Tie Width, PA66STHS, Black, 1000/pkg

|                     |                                                                                                                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 151-30001                                                                                                                                                                                                       |
| Type                | MMB.5                                                                                                                                                                                                           |
| Color               | Black (BK)                                                                                                                                                                                                      |
| Quantity Per        | bag                                                                                                                                                                                                             |
| Product Description | HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications. |
| Short Description   | Masonry Cable Tie Mount, 1.24"L, 0.25" Hole Dia, 0.18" Max Cable Tie Width, PA66STHS, Black, 1000/pkg                                                                                                           |
| Global Part Name    | MMB.5-PA66STHS-BK                                                                                                                                                                                               |

|                                       |                        |
|---------------------------------------|------------------------|
| Length L (Imperial)                   | 1.24                   |
| Length L (Metric)                     | 31.5                   |
| Fixation Method                       | with Fir Tree (Mounts) |
| Width W (Imperial)                    | 0.375                  |
| Width W (Metric)                      | 9.5                    |
| Cable Ties                            | T18 - T50              |
| Height H (Imperial)                   | .37                    |
| Height H (Metric)                     | 9.40                   |
| Cable Tie Width Max (Imperial)        | 0.18                   |
| Cable Tie Width Max (Metric)          | 4.6                    |
| Panel Thickness Min (Imperial)        | 1.0                    |
| Panel Thickness Min (Metric)          | 25.4                   |
| Panel Thickness Max (Metric)          | 25.4                   |
| Mounting Hole Diameter D (Imperial)   | 0.25                   |
| Mounting Hole Diameter D (Metric)     | 6.35 mm                |
| Mounting Hole Diameter D Max (Metric) | 6.35                   |

|                              |                                                        |
|------------------------------|--------------------------------------------------------|
| Material                     | Polyamide 6.6, super tough, heat stabilized (PA66STHS) |
| Material Shortcut            | PA66STHS                                               |
| Flammability                 | UL 94 HB                                               |
| UV Resistant (Yes/No)        | No                                                     |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)                      |
| Reach Compliant (Article 33) | No                                                     |
| ROHS Compliant               | Yes                                                    |
| Package Quantity (Imperial)  | 1000                                                   |
| Package Quantity (Metric)    | 1000                                                   |
| Customs Number               | 3926909988                                             |