

Specification Sheet

Part Number: RTT750HR.NX1P



The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.

Additional design feature on the head allows excess strap to be tucked away after installation.

Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 25/pkg

Article Number	115-00000
----------------	-----------

Type	SpeedyTie (RTT750HR)
------	----------------------

Color	Red (RD) Yellow (YE)
-------	----------------------

Quantity Per	bag
--------------	-----

Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.
---------------------	--

Short Description	Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 25/pkg
-------------------	---

Global Part Name	SpeedyTie (RTT750HR)-PA66-RD/YE
------------------	---------------------------------

Minimum Tensile Strength (Imperial)	200.0
Minimum Tensile Strength (Metric)	888.0
Length L (Imperial)	29.6
Length L (Metric)	752.0
Identification Plate Position	none
Releasable Closure	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.51
Width W (Metric)	13.0
Bundle Diameter Min (Imperial)	1.6
Bundle Diameter Min (Metric)	40.0
Bundle Diameter Max (Imperial)	8.3
Bundle Diameter Max (Metric)	210.0
Thickness T (Imperial)	0.075
Thickness T (Metric)	1.9

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988